

MX-62

6-Channel Mixer

OPERATING MANUAL

***Thank you for purchasing an Azden product.
Please read this manual thoroughly before using this
product.***



SPECIFICATIONS

INPUT

LINE/MIC-HI/MIC-LO (electric balance)	XLR-3 pin (female) x 6 (CH 1, CH2, CH 3, CH 4, CH 5, CH 6)
AUX (unbalance)	RCA pin (female, L/R) x 2 (AUX 1, AUX 2)
EXT (electric balance)	XLR-3 pin (female) x 2 (L ch, R ch)

INPUT	LINE	MIC-HI	MIC-LO	AUX	EXT IN
STANDARD INPUT LEVEL	+ 4dBu	-	-	- 4dBu	+ 4dBu
MAX. GAIN	+ 19dB	+ 47dB	+ 66dB	+ 25dB	+ 0dB
MAX. INPUT LEVEL	+ 22dBu	- 6dBu	- 24dBu	+ 16dBu	+ 22dBu
INPUT IMPEDANCE	16k	5k	4.6k	9k	18k

OUTPUT

LINE (electric balance)	XLR-3 pin (male) x 2 (L ch, R ch)
LOAD IMPEDANCE	more than 600
OUTPUT LEVEL	+4dBu
MAX. OUTPUT LEVEL	more than +22dBu (load 10k @ 1%) more than +20.5dBu (load 600 @ 1%)
OUTPUT IMPEDANCE	94
VU METER LEVEL	+4dBu (0VU)
Hi-pass filter(HPF) cut off frequency, gradient	100Hz, 6dB / oct

Limiter Operating Pressure

Output level when not operating	Operating Pressure
+26dBu	5.6dB
+22dBu	3.6dB
+15dBu	1.5dB
+4dBu	0.2dB

Phantom power 48 ± 2V

GENERAL FEATURES

FREQUENCY	20Hz - 30kHz (+0/less than -0.5dB)
INPUT NOISE LEVEL (single CH input)	
MIC-LO	less than -127dBu (+66dB gain, A weighted)
OUTPUT DYNAMIC RANGE (single CH input)	
LINE	more than 107dB (0dB gain, A weighted)
AUX/EXT	more than 110dB (0 dB gain, A weighted)
THD+N (1kHz, max. -1dB input)	
LINE/MIC-HI/AUX/EXT	less than 0.003% (load 10k , +21dBu output)
MIC-LO	less than 0.006% (load 10k , +21dBu output)
POWER	DC 12V
POWER CONSUMPTION	9W
SIZE	W 435 x D 210 x H 44 (mm)
WEIGHT	approx. 2.25kg

6 Channel Mixer MX-62

This is a 1U sized mixer supported 6ch balance line/microphone input, stereo audio input with 2 RCA L/R connector systems, EXT input which mixes the balance line L/R audio directly, and a balance line L/R output.

It also has a phantom power supply, limiter, hi-pass filter, PAN function of output signal, and an input peak indicator with a VU meter.

Main Features

- Individual switches on every channel of XLR balance input; mic level (HI/LO) or +4dBu standard line level.
- RCA pin AUX input which enables unbalance stereo signal input in 2 systems.
- EXT input mixes the XLR balance line L/R signal directly.
- XLR balance line L/R output is +4dBu standard line level.
- Phantom power supply of 48V, with an individual ON/OFF switches on every channel (MIC).
- Each channel has an input peak indicator to show the excess input (LINE/MIC,AUX).
- Limiter function manages the excessive level while mixing; each channel has an individual ON/OFF switch (LINE/MIC).
- Each channel has a hi-pass filter switch to cut the input signal under 100Hz (LINE/MIC) .
- Individual PAN function switch to control or stabilize the output balance of L ch and R ch of each input channel signal (LINE/MIC).
- XLR balance line L/R output level is shown on a peak indicator with a VU meter.
- Channel fader to control the mix level of each input channel signal, and a master fader to control the line output level (LINE/MIC,AUX).
- VU meter can be lit up

PartS(Front Control)


Power switch / Power indicator	Turns power ON/OFF / When power is ON, the red light will light up
CH 1, 2, 3, 4, 5, 6 input volume	Adjusts the mix level volume of input signal from CH1 - 6
CH 1, 2, 3, 4, 5, 6 PAN volume	Control or stabilize the output balance of L ch and R ch of each input channel signal
AUX1, 2 volume	Adjusts the RCA pin AUX input level of 2 systems
MASTER volume	Adjusts the level of line out output (If set to the center, the output amp gain is ± 0)
CH 1, 2, 3, 4, 5, 6 LIMITER switch	Turns limiter function ON/OFF of CH 1 - 6 (When the function is ON, it suppresses the sound of excessive input level without clipping)
CH 1, 2, 3, 4, 5, 6 HPF switch	Turns Hi-pass filter function of CH 1 - 6 ON/OFF (If set to ON, it cuts the input signal under 100Hz)
INPUT PEAK indicator	The indicator lights up in red when distorted by excess signal. This device has INPUT 1 & INPUT 2 indicators. When both indicators light up, it indicates below status;

CH1, R VU meter	Analog VU meter which shows the line out output. Adjust the input signal level by input volume or adjust the output signal level by MASTER volume; do not let it be off the scale, or let the output peak indicator's light up.
CH1, R OUTPUT PEAK indicator	Monitors the line out output. Lights up in red when distorted by excessive output signal level. When light up in red, adjust the input volume or adjust the output signal level by MASTER volume.
INPUT LEVEL switch	3 types of input level can be chosen by connecting source to an input connector. INPUT LEVEL (LINE) - Standard input level : +4dBu Maximum input level : +22dBu (16k) INPUT LEVEL (MIC HI) - Maximum input level : -6dBu (5k) INPUT LEVEL (MIC LO) - Maximum input level : -24dBu (4.6k)
PHANTOM switch	Turns the power of phantom power +48v ON/OFF. It can supply a MIC power +48v when ON. It can only be used when MIC input is selected (INPUT LEVEL switch : MIC HI/ MIC LO). Please turn OFF when no need of the phantom power. Before turning on the phantom power, please confirm if the connecting device is compliant to phantom power. When turning the switch ON / OFF, please adjust the volume to 0 all the time.
PEAK 1 indicator	Excessive signal is being inputted. Configuration of standard input or INPUT LEVEL SW against the input source may be faulty. Please try to change the configuration using INPUT LEVEL SW. If the light is still lit up, the device is inputting signal excessively. Please adjust the output level of connecting device.
PEAK 2 indicator	Mixing signal level is too high. Please adjust the signal level by Input volume.
AUX INPUT PEAK indicator	The indicator lights up in red when distorted by excess signal. Adjust the signal level of mixing signal by input volume.


(Rear Panel)	CH1, 2, 3, 4, 5, 6 XLR input connector Suitable input sensitivity for the input source can be set by INPUT LEVEL switch
AUX 1, 2 input connector	RCA pin AUX input which enables unbalance stereo signal input to 2 systems
EXT IN connector / ON-OFF switch	EXT input ON/OFF switch mixes the XLR balance line L/R signal directly.
CH1 XLR output connector	CH1 XLR output connector Outputs the mixed L ch signal. Output level is +4dBu (LINE OUT).
DC 12V jack	DC 12V jack Use the standard packed ac/dc adapter

Parts

Front Control



Rear Panel



TWO-YEAR WARRANTY

Azden Corporation warrants, to the first purchaser, that the Azden brand product purchased is free from defects in material and workmanship. Azden's sole obligation under this warranty shall be to provide, without charge, repair or replacement (at Azden's option), within two years from the date of purchase. A dated receipt acts to establish the date of purchase.

This warranty is the sole and exclusive express warranty given with respect to the product and all other express warranties are hereby excluded. Neither AZDEN, nor the dealer who sells this product, is responsible for indirect, incidental or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation may not apply to you.

This warranty does not extend to any defect, malfunction or failure caused by misuse, abuse, accident, faulty hookup, unauthorized modification or defective associated equipment for which it is not intended. Please read your owner's manual carefully.

This warranty gives you specific legal rights. You may also have other rights which vary from state to state.

To register this product, go to www.azdencorp.com/warranty "for North/South America and EU customers.

Asia/Oceania customers contact with Azden distributors listed on www.azden.co.jp/global.html

Customers in the Asian and Oceania markets contact:
Azden Corp., 1-12-17 Kamirenjaku Mitaka-shi, Tokyo, 181-8533 Japan
voice - 81-0-422-55-5115(Japan) • fax - 81-0-422-55-0131(Japan)

email - sales@azden.co.jp

Customers in the North/South America and European markets contact:
Azden Corp., 200 Valley Road, Suite 101, Mt. Arlington, NJ 07856
voice - 973-810-3070 • fax - 973-810-3076 • email - azdenus@azdencorp.com